

Item Description	Jed. more	NEW ORDER QTY	unit price	Total
Siren, outdoor mounting. Steel enclosure of thickness 1,5 mm tamper proof against opening	pcs	6	118.01	708.07
Keypad, LCD touch screen 14cm in diagonal. The touch screen provides a durable graphic	pcs	18	290.28	5,225.04
Battery, 12 VDC, 40Ah.	pcs	2	115.30	230.60
- optical patch cord E2000/APC - LC duplex G657.A1,length 50m, LSZH	pcs	16	23.34	373.43
Manual call point for stopping of the extinguishing CCP-B	pcs	4	34.59	138.36
Aspirational smoke detector for computer racks in room with space for two detection	pcs	6	4,771.99	28,631.94
IP Panoramic ceiling ONVIF 5Mpix camera with 1/3- inch CMOS and lens 360 ° Fisheye	pcs	4	520.88	2,083.51
Electromagnetic door holder, 12/24Vdc, maximum load of 300kg. With a door status	pcs	4	73.93	295.71
Magnetic contact for monitoring the fire door status,i.e. whether the fire door is open or closed,	pcs	4	33.91	135.64
- optical patch cord E2000/APC - LC duplexG657.A1, length 50m, LSZH	pcs	4	23.34	93.36
Manual call point for stopping of the extinguishing CCP-B	pcs	2	34.59	69.18
IP ONVIF Day / Night full HD camera, 1 / 2.9" CMOS HD 3072 x 1728 (5MP) sensor with built-in	pcs	3	302.49	907.46
IP Panoramic ceiling ONVIF 5Mpix camera with 1/3- inch CMOS and lens 360 ° Fisheye	pcs	3	520.88	1,562.63
JH(St)H 2x2x0.8	m	950	0.23	214.05
Siren, outdoor mounting. Steel enclosure of thickness 1,5 mm tamper proof against opening	pcs	1	118.01	118.01
Addressable optical smoke detector that supports EN54 and VdS standard. Complete with	pcs	21	42.05	883.05
Magnetic contact for monitoring the fire door status,i.e. whether the fire door is open or closed,	pcs	3	33.91	101.73
- optical patch cord E2000/APC - LC duplexG657.A1, length 50m, LSZH	pcs	6	23.34	140.03
- J-H(St)H 2x2x0,8	m	480	0.23	108.15
IP ONVIF Day / Night full HD 1080p camera, 1/3 "CMOS HD 2048 x 1536 (3MP) sensor with	pcs	8	719.60	5,756.77
Adapter for mounting a dome camera on the wall (BOSCH VDA-832FHD-WMT or equivalent)	pcs	8	57.65	461.19

IP Panoramic ceiling ONVIF 5Mpix camera with 1/3- inch CMOS and lens 360 ° Fisheye	pcs	2	520.88	1,041.75
JH(St)H 2x2x0.8	m	700	0.23	157.72
JH(St)H 5x2x0.8	m	480	0.58	280.42
Battery, 12 VDC, 40Ah.	pcs	4	2.71	10.85
Addressable optical smoke detector that supports EN54 and VdS standard. Complete with	pcs	26	42.05	1,093.30
Addressable module with 2 independently programmable high-voltage relay outputs and 2	pcs	1	126.15	126.15
Magnetic contact for monitoring the fire door status,i.e. whether the fire door is open or closed.	pcs	2	33.91	67.82
Additional base for fixing the fire detector on non- standard surfaces (concrete beams, roof	pcs	1	12.89	12.89
- optical patch cord E2000/APC - LC duplexG657.A1, length 50m, LSZH	pcs	4	23.34	93.36
- J-H(St)H 2x2x0,8	m	320	0.23	72.10

51,194.26